



Specialty Adhesives and Coatings

TECHNICAL DATA SHEET

PRODUCT DESIGNATION: PS 149

VALPAC PS-149 is a solvent rubber-based removable pressure sensitive adhesive. This type of product is used for removable masking films. It will adhere to painted surfaces and remove cleanly without residue. Has broad FDA compliance. (see your technical representative for details)

TYPICAL PHYSICAL AND APPLICATION DATA

Viscosity (4 @ 20 rpm):.....2500- 5500 cps.
Weight/Gallon @ 77°F (25°C):.....5.8 – 6.0 lbs/gallon
% Solids:.....13.5 – 14.5%
Solvent.....Heptane

COATING PROCEDURE: PS 149 can be applied using gravure, air knife, roll coater, Meyer rods, and many other types of coating equipment.

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. **NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.** Nothing herein is to be taken as permission, inducement or recommendation to practice any invention or existing patent without a license. Revision: 01/09

**1400 Industrial Park Road
Federalsburg, MD 21632
Tel 410-754-7390 www.valpac.com Fax 410-754-7541**