



Specialty Adhesives and Coatings

TECHNICAL DATA SHEET

PRODUCT DESIGNATION: PS 793

GENERAL DESCRIPTION: PS 793 is a water-based acrylic removable pressure sensitive adhesive. This low tack adhesive is ideal for masking film applications. When crosslinked, PS 793 offers excellent water resistance and clean remove ability from polished metal as well as a wide variety of other substrates.

TYPICAL PHYSICAL AND APPLICATION DATA

Viscosity @ 77°F (25°C):.....600 - 900 cps. (Brookfield RVT #4 spindle @ 20 rpm)
Weight/Gallon @ 77°F (25°C):.....8.6 lbs.
pH:.....7.4 – 8.6
% Solids:.....42 – 43

COATING PROCEDURE: PS 793 should be thoroughly mixed with the Valpac XL series cross-linker prior to use. PS 793 can be applied using gravure, air knife, roll coater, Mayer rods, and many other types of coating equipment. Films coated with PS 793 must be completely dried before rewinding.

The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. **NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.** Nothing herein is to be taken as permission, inducement or recommendation to practice any invention without a license. Revision: 02/04

1400 Industrial Park Road
Federalsburg, MD 21632

Tel 410-754-7390

www.valpac.com

Fax 410-754-7541